



[www.freedomlift.com](http://www.freedomlift.com)

The Best Solution To Carry Your Tender  
or Personal Water Craft (PWC)!





[www.freedomlift.com](http://www.freedomlift.com)





## Finally, a hydraulic lift that is removable!

- More comfortable and easier access to and from tender/PWC
- Does not effect the use of the swim platform/bathing deck
- Simple wireless remote control
- Easily removable Lift Arms!
- Easy installation
- Fits multiple boat types



United States Patent # 6,474,256

Toll Free: 1-866-543-8669

# The most care-free, time-saving lift on the market!

## The ONLY lift with easily Removable Lift Arms.

**FreedomLift®** weighs less than 320 lbs (145kg). Light-weight Lift Arms translate into safe one-person operation. And, Lift Arms are stored when not in use.

Enjoy the freedom. Enjoy YOUR freedom.

**FreedomLift®** features hydraulic wireless remote-control operation - just the touch of a button and you are on your way. So, whereas many lifts require a tremendous amount of time and effort, with **FreedomLift®** you enjoy the freedom to:

- Transport and use your tender when and where you want - with just the touch of a button!
- Operate your yacht without the hindrance of bulky, cumbersome and unsightly lift parts
- Remove the Lift Arms when not carrying your tender
- Have more fun and work less.

## Installs independent of your swim platform; no hull modifications necessary.

Unlike old style platform lifts, with **FreedomLift®** you keep your boat just as it is. No more replacing the factory-designed platform, no more ruining the design lines of your boat, no longer lose the use of your swim platform.

**FreedomLift®** mounts externally to the transom, hidden from sight under the swim platform. No modification to the existing hull or swim platform is necessary.



**FreedomLift®** is manufactured using only the highest quality components and materials and is designed to enhance your boating experience.

- Load is distributed over 360 square inches (0.23 m<sup>2</sup>) of transom space.
- Dual hydraulic cylinders.
- Elliptical motion provides 44" (111.8 cm) of vertical travel and 12" (30.5 cm) retraction over swim platform.
- Carrying capacity up to 800 lbs (360kg).
- Keeps your tender out of the water at all speeds.





# Designed, developed and manufactured utilizing nearly 20 years of expertise in marine hydraulic lifts.

**FreedomLift®** is manufactured with the finest quality parts - strong, lightweight marine-grade alloy and stainless steel hardware, a premium Hydraulic Power Unit system with environmentally safe fluid, and wireless remote (waterproof) control operation. The two hydraulic lift assemblies are interconnected by a structural cross member assembly, ensuring the integrity of the lift and providing smooth, uniform movement of both Arms despite any uneven weight distribution. **FreedomLift®** is designed to fit/work on most boats, with little or no adjustments necessary.

## Construction Properties

- Constructed utilizing Marine Grade 6061-T6 aluminum alloy or stainless steel
- Braided stainless steel hydraulic lines
- Environmentally safe hydraulic fluid
- 100% 316 Stainless Steel hardware
- Dual hydraulic cylinders
- Sealed 12 or 24 volt Hydraulic Power Unit with Certified Ignition Protection
- Marine rated finish including Cathodic Epoxy Electrocoat (E-Coat) plus Marine Rated Powder Coating
- CNC precision machined
- No transom modification required for installation
- Total unit weight of 320 lbs (145kg)
- 316 Stainless Steel hydraulic cylinders (Optional)
- Carbon fiber bushings

## Design Features

- 44" (111.8 cm) of Lifting Range - Best In Class
- Capacity rated to carry tenders and PWC up to 800 lbs (360kg)
- Computer Aided Design (CAD) / Computer Aided Manufacturing (CAM) design build
- Fully adjustable Removable Lift Arms to accommodate virtually any inflatable tender, RIB or PWC
- Back-up corded controller
- Self-contained Hydraulic Power Unit
- Safe 12 or 24 volt DC operation
- Internal flow control valve
- Automatic locking system with manual release
- Hydraulic cylinder retracted in upright and locked position
- Anodes are included

## Operation Advantages

- Removable Lift Arms
- No need to remove engine or accessories from tender
- Wireless remote-control operation
- Safe, one-person operation
- Less than 15 second lift or launch time
- Two year limited warranty



**Toll Free: 1-866-543-8669**

Azimut  
Bayliner  
Bertram  
Bluewater  
Blue Star  
Cabo  
Carver

Chris Craft  
Cruisers  
Dyna Craft  
Egg Harbor  
Four Winns  
Grand Banks Eastbay  
Gibson

Hampton  
Hans Christian  
Hatteras  
Jefferson  
Leopard  
Mainship  
Matthews

Recent ***FreedomLift***® installations

Maxum  
Meridian  
Navigator  
Neptunus  
Nordic Tugs  
Ocean Alexander  
Ocean Yachts

Princess  
Rampage  
Regal  
Riviera  
Sabre Yachts  
Sea Ray  
Sealine

Silverton  
Sonship  
Sunseeker  
Tiara  
Tollycraft  
Viking  
Wesmac

***"...We stopped at 19 different ports and we used the dinghy at 15 of them. The "freedom" the FreedomLift gave us added a whole different dimension to our trip..."***

LOU GAGLIARDI, SILVERTON 39 MY

***"...For anyone who has shopped hydraulic lift platforms, the FreedomLift system is a true bargain in comparison..."***

RICK SHEERAN, REGAL 4460

Recent notes from ***FreedomLift®*** customers

***"...the quality and the reliability of the FreedomLift has added great fun to our boating adventures with our tender..."***

JIM MESTDAGH, BERTRAM 63

***"...I would never own another yacht without the FreedomLift installed..."***

RON COHEN, AZIMUT 62

***FULL CUSTOMER TESTIMONIALS AVAILABLE ON OUR WEBSITE***

**Toll Free: 1-866-543-8669**

*See our dynamic video website at [www.freedomlift.com](http://www.freedomlift.com)*



If you have any questions or would like additional information,  
please contact us at our toll-free number or:

[sales@freedomlift.com](mailto:sales@freedomlift.com)

[service@freedomlift.com](mailto:service@freedomlift.com)

Fax: 616-784-0349

929 Alpine Commerce Park NW, Suite 300  
Grand Rapids, MI 49544-8232



**Toll Free: 1-866-543-8669**